

WEIGHING TRANSMITTER GT202



Multi channel anti-interference version
/ Advanced multi channel version



Advanced single channel version
/ Single channel anti-interference version



Single channel version

FEATURES

1. Parallel connect 2-6 load cells directly, each load cell could be calibrated dependently;
2. Surge protection function;
3. Input reverse connection protection and output protection;
4. Current/ voltage output;
5. Cable connector and aviation plug is used for cable connections;
6. Could be mounted on platform with the mounting holes of housing.
7. Anti-interference version could resist harmonic interference of inverter or other devices;

SPECIFICATION

Rated input	0-20mV
Rated output	0-5V/ 0-10V/ 0-±5V/ 0-±10V/ 4-20mA
	Could output 0-5V, 4-20mA at same time
Accuracy	≤ ±0.05-0.1%F.S
Voltage	12/ 24VDC
Operation temp.	-20~85℃
Ingress protection	IP65 (Advanced and anti-interference version)

TYPE SELECTION

Model	Item	Material	Size (mm)	Other function
GT202-1	Single channel version	Iron	112x45x33	--
GT202-2	Advanced single channel version	Alloy aluminum	110x64x37	Water and dust proof
GT202-3	Single channel anti-interference version	Alloy aluminum	110x64x37	Water and dust proof
GT202-4	Multi channel anti-interference version	Alloy aluminum	158x100x65	Water and dust proof