

# Platform Scale Indicator



## GSI401-2



### INTRODUCTION

The GSI401-2 indicator can be used in connection with single or multiple load cells, and directly display the weighing value through the A/D conversion principle. The indicator is AC and DC supply power dual-use, stainless steel material, 6-digit 0.8-inch green LED display, mainly suitable for electronic platform scales, electronic floor scales and other related scales.

### PRODUCT FUNCTION

- Manual/automatic accumulation function ;
- Zero tracking range can be selected ;
- Filter time parameters can be set ;
- Power saving mode optional ;
- Sufficient battery power can be used continuously for more than 30 hours ;
- 10 times more accurate display ;
- Kg-lb conversion ;
- Animal Scale Function ;
- Count function ;
- Peak hold function ;
- Printing function ;

**TECHNICAL PARAMETER** ///

|                                  |                                |
|----------------------------------|--------------------------------|
| Accuracy                         | 1/3000                         |
| Display accuracy                 | 1/3000 ~ 1/30000               |
| Load cell excitation voltage     | 5V DC                          |
| Supply power                     | 100 ~ 240VAC 50HZ              |
| Battery                          | Lead-acid , 6V/2.8AH           |
| Max number of connected sensors  | 350Ω 1 ~ 4pcs or 700Ω 1 ~ 8pcs |
| Working temp. range              | -10℃ ~ +40℃                    |
| Storage temperature and humidity | -25℃ ~ +55℃ , ≤85%RH           |
| Communication                    | RS232 , RS485(optional)        |
| Baud rate                        | 1200/2400/4800/9600            |